

Water Block Setting Guide*

*Estimated only, consult the equipment installation guide for your specific equipment. Not recommended for Cuber Ice Machines > 750 lbs, Steam Ovens >, Rack and Conveyor Dish Machines

Application	Type of Equipment	Flow Rate (GPM)	Consumption (Gallons)	Suggested Dial Setting	Potential Water Spillage Before Shut Off (Gallons)
Drinking Water	POU Cooler	0.50		2	
	Drinking Water Fountain	0.13-1.5		4(set to group size)	
Drip (filter) Coffee	1/2 Gallon Glass Carafe	0.50	0.5	1	0.5-1
	Single Airpot	0.50		1	0.5-1.0
	Dual Airpot	1.00		2	1.0-2.0
	Sattelite Brewers	1.00		3	2.0-3.0
Espresso Coffee	Super Automatic	0.50		1	.75-1.5
	Single Group Head	0.50		1	.75-1.5
	Twin or Triple Group Head	1.00		2	
Fountain Beverage	5-6 valve Dispenser	1.67-3.34			
	8-valve Dispenser	1.67-3.34			
	12-valve Dispenser	1.67-5.01			
Frozen Carbonated (FCB)	2-4 Flavors	1.0-1.67		2	1.0-2.0
	6-8 Flavors	1.0-1.67		2	1.0-2.0
Iced Tea	1.5-Gallon Brewer	1.0-1.5	1.5	2	1.5-2
	3-Gallon Brewer	1.0-1.5		4	2-2.5
	5-Gallon Brewer	1.0-1.5		5	1-2.5
Ice - Low Flow Cube	Undercounter	0.5-1.0		2	1.0-2.0
	250-500 lbs	0.5-1.0		2	1.0-2.0
	501-750 lbs	0.5-1.0		3	1.0-2.0
Ice - High Flow Cube	Undercounter	0.5-1.0		1	1.0-2.0
	250-500 lbs	1.0-2.5		2	1.0-2.0
	501-750 lbs	2.5-4.0		3	1.0-2.0
Ice - Flaker/Nugget	Undercounter	0.50		1	1.0-2.0
	100-500 lbs	0.50		1	1.0-2.0
	501-750 lbs	0.50		3	1.0-2.0
Steam - BTU	<125,000 BTU	0.5-3.0	1	2	1.0-2.0
	125,000-200,000 BTU	0.5-3.0	2	3	1.0-2.0
	200,000-300,000 BTU	0.5-3.0	5	5	1.0-2.5
Steam - kW	2-3 kW	0.5-3.0	1	2	1.0-2.0
	4-10 kW	0.5-3.0	1	2	1.0-2.0
	11-24 kW	0.5-3.0	2	3	1.0-2.0
	25-36 kW	0.5-3.0	2	3	1.0-2.0
	49-58 kW	0.5-3.0	5	5	1.0-2.5
	60-70 kW	0.5-3.0	5	5	1.0-2.5
Dish Machine	Undercounter	7.00	3 to 7 based on model		
	Glass Washer	7.00	3 to 7 based on model		
	Door Type	7.0-23.0		based on model.	