

Specification table for the CL-Series inline filters, OCB elements and CS elements.

Every Omnipure filter undergoes rigorous testing and independent verification for performance. Each filter is rated at .5 gpm with a maximum pressure of 125 psi and a maximum temperature of 100° F. Chlorine reduction Class 1.

| Description Application | Model Number | Filter Length | Volume Cubic Inch | Service Life Gal. or 1 year | Degree of Nominal Filtration | Pipe Size NPT | Reduction Class |
|--|--------------|---------------|-------------------|-----------------------------|------------------------------|---------------|-----------------|
| Taste and odor reduction down to 10 microns. | CL6ST T28 | 6" | 8.3 | 1000 | 10 microns | 1/8, 1/4, 3/8 | 1 |
| | CL10ST T28 | 10" | 16.6 | 1500 | 10 microns | 1/8, 1/4, 3/8 | 1 |
| Granular activated Carbon | CL6ST T33 | 6" | 8.3 | 1000 | 10 microns | 1/8, 1/4, 3/8 | 1 |
| | CL10ST T33 | 10" | 16.6 | 1500 | 10 microns | 1/8, 1/4, 3/8 | 1 |
| Dirt, sand and sediment removal. Polypropylene | CL6PF5 | 6" | NA | NA | 5 microns | 1/8, 1/4, 3/8 | 2 |
| depth filtration. Filters | CL10PF5 | 10" | NA | NA | 5 microns | 1/8, 1/4, 3/8 | 2 |
| down to 5 microns. | CL6PF25 | 6" | NA | NA | 25 microns | 1/8, 1/4, 3/8 | NA |
| | CL10PF25 | 10" | NA | NA | 25 microns | 1/8, 1/4, 3/8 | NA |
| Taste and odor reduction. Specifically designed for | CL6RO T28 | 6" | 8.3 | 1000 | 5 microns | 1/8, 1/4, 3/8 | 1 |
| R.O. or distillation units. | CL10RO T28 | 10" | 16.6 | 1500 | 5 microns | 1/8, 1/4, 3/8 | 1 |
| | CL6RO T33 | 6" | 8.3 | 1000 | 5 microns | 1/8, 1/4, 3/8 | 1 |
| Granular activated carbon. | CL10RO T33 | 10" | 16.6 | 1500 | 5 microns | 1/8, 1/4, 3/8 | 1 |
| Taste and odor reduction. | SCL6 | 6" | 8.3 | 750 gal. or 6 months | 10 microns | 1/8, 1/4, 3/8 | 1 |
| Equipment scaling protection. | SCL10 | 10" | 16.6 | 1250 gal. or 6 months | 10 microns | 1/8, 1/4, 3/8 | 1 |
| Replacement cartridges for standard housings. Taste | OCB934STT28 | 9-3/4 | 56 | 5000 | 10 microns | NA | NA |
| and odor reduction. GAC. | OCB934ROT28 | 9-3/4 | 56 | 5000 | 5 microns | NA | NA |
| | OCB934ROT33 | 9-3/4 | 56 | 5000 | 5 microns | NA | NA |
| Replacement cartridges for slim line housings. Taste | CS934T28 | 9-3/4 | 35 | 3000 | 10 microns | NA | NA |
| and odor reduction. GAC. | CS934T33 | 9-3/4 | 35 | 3000 | 10 microns | NA | NA |

Test Information: The CL-Series filter housing and fittings have been tested for performance under NSF Standard 42. Tests included *Hydro Static Testing* at 300 psig and *Cycle Testing* of 100,000 repetitions from 0 to 150 psig. Complete test results are available from OMNIPURE. Omnipure products have been tested and listed under Standard 42 for taste, odor and chlorine reduction; or particulate reduction; or have been materials certified. All filters should be installed on cold water lines only. **NOTE:** Activated carbon filters are not intended to be used where the water is microbiologically unsafe or with water of unknown quality without adequate disinfection before or after the unit.

Warranty Information: Omnipure Filter Company (Omnipure) warrants that the products delivered will be free from any defects in workmanship or materials. Further, the warranty provided herein applies, only when used within the products specifications and service life, from the date of installation, beyond which time or use Omnipure is absolved of any and all liability for any use of the product. In the event of defect or non-conformity, buyer shall promptly notify Omnipure in writing, supplying proof of purchase dates, installation dates, and will protect and retain the products for investigation or Omnipure is absolved of any and all liability for any use of the product. There are no other warranties, either merchantability or fitness, either expressed or implied.