

SHURFLO® WATER PRESSURE REDUCER VALVES (WPRV)

Shurflo Water Pressure Reducer Valves (WPRV) are fixed pressure water-reducing devices (non-adjustable). The WPRV minimizes incoming water pressure

fluctuations while guarding against pressure spikes. Actual pressure reduction is dependent upon input pressure and outlet flow rate.



A



B



C



D



E



F

PART NO	DESCRIPTION	CASE QTY.	LIST PRICE
A 183-130-SS	30 PSI [2.1 BAR], Water Pressure Reducer Valve, inlet/outlet: 3/8" [10 mm] barb, stainless steel fittings	30	\$38.30
B 183-150-PG	50 PSI [3.4 BAR], Water Pressure Reducer Valve, inlet/outlet: 3/8" [10 mm] barb, stainless steel fittings, stainless steel body and pressure gauge with follower	6	85.80
A 183-150-SS	50 PSI [3.4 BAR], Water Pressure Reducer Valve, inlet/outlet: 3/8" [10 mm] barb, stainless steel fittings	30	38.30
C 183-150-01	50 PSI [3.4 BAR], Water Pressure Reducer Valve, inlet/outlet: 3/8" [10 mm] barb, stainless steel fittings, stainless steel body	30	56.30
A 183-165-SS	65 PSI [4.5 BAR], Water Pressure Reducer Valve, inlet/outlet: 3/8" [10 mm] barb, stainless steel fittings	30	38.30
C 183-165-01	65 PSI [4.5 BAR], Water Pressure Reducer Valve, inlet/outlet: 3/8" [10 mm] barb, stainless steel fittings, stainless steel body	30	56.30
B 183-165-02	65 PSI [4.5 BAR], Water Pressure Reducer Valve, inlet/outlet: 3/8" [10 mm] barb, stainless steel fittings, stainless steel body and pressure gauge with follower	6	85.80
A 183-180-SS	80 PSI [5.5 BAR], Water Pressure Reducer Valve, inlet/outlet: 3/8" [10 mm] barb, stainless steel fittings	30	38.30
C 183-180-01	80 PSI [5.5 BAR], Water Pressure Reducer Valve, inlet/outlet: 3/8" [10 mm] barb, stainless steel fittings, stainless steel body	30	56.30
B 183-180-02	80 PSI [5.5 BAR], Water Pressure Reducer Valve, inlet/outlet: 3/8" [10 mm] barb, stainless steel fittings, stainless steel body and pressure gauge with follower	6	85.80
E 183-130-NF	30 PSI [2.1 BAR], Water Pressure Reducer Valve, w/o fittings	12	35.30
E 183-150-NF	50 PSI [3.4 BAR], Water Pressure Reducer Valve, w/o fittings	12	35.30
E 183-165-NF	65 PSI [4.5 BAR], Water Pressure Reducer Valve, w/o fittings	12	35.30
D 183-165-QC14	65 PSI [4.5 BAR], Water Pressure Reducer Valve, 1/4" [6.4 mm] John Guest® fittings	12	44.70
D 183-165-QC38	65 PSI [4.5 BAR], Water Pressure Reducer Valve, 3/8" [10 mm] John Guest fittings	12	44.70
F EV313526	Pair of 1/2" [12.7 mm] and 1/4" [6.4 mm] John Guest fittings	12	22.70
F EV313527	Pair of 1/2" [12.7 mm] and 1/3" [8.5 mm] John Guest fittings	12	22.70